



uFace 302



► Multi-Biometric Time Attendance & Access Control System

Storage Capacity

Face Capacity : 3,000
Fingerprints Capacity : 4,000
ID Card Capacity : 10,000
Transaction Capacity : 1,00,000
Push Data : Yes
Communication : TCP/IP, RS232/485,
USB Host, WiFi, 3G
Display : 4.3-Inch Touch Screen

Standard Functions

Automatic Status Switch, Self-Service Query, Work Code, SMS, DST,
T9 Input, 9 Digit User ID, Scheduled Bell,
Photo ID Access Control Interfaces for: 3rd Party
Electric Lock, Door Sensor, Exit Button, Alarm
Wiegand : Output

Optional Functions

MiFare Card, Wi-Fi, 3G,
2000 mAh Backup Battery, FR-1200

Power & Environment

Power Supply : 12V 3A
Operating Temperature : 0 °C ~ 45 °C
Operating Humidity : 20% - 80%
Dimension (in mm) : 193.6 x 165.2 x 86
Package Weight : 1.6 kg

Features

- Multi-languages
- High verification speed
- Advanced and user-friendly UI
- Chip encryption for firmware protection
- Optional built-in battery backup providing approximately 4 hours of continuous operation
- Easy to extend functions and customize client's requirements
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification